

Productsheet

BAMFLOORI NATURAL FLOORING

EUROPEAN GRADING

1-bis The 1-bis grading is the calmest grading, containing only small knots. The knots are approximately 22mm in size. Naturally, being a natural product, there may be slight variations.

A In this grading, slightly larger knots are allowed. The knots in the A grading are approximately 50mm in size. Naturally, being a natural product, there may be slight variations.

AB In this grading, the A knots are around 50mm in size, and the B knots are around 80mm in size. Naturally, being a natural product, there may be slight variations.

Rustic The rustic grading is the most lively grading. In the rustic grading, knots of all sizes and sapwood are allowed. Sapwood refers to the softer wood. It cannot be oiled.



GENERAL INFORMATION:

Construction: Oak Multi plank floors are composed of different layers of wood. The top layer is usually solid oak, while the lower layers consist of plywood.

The used plywood layers provide stability and prevent the floor from warping or cracking.

Oak Wood: Oak wood is a popular wood species due to its durability and natural beauty. It has a distinctive grain structure and a warm appearance. Oak Multi plank floors offer the beauty of solid oak wood with the stability of a multi-layered construction.

Installation: Oak Multi plank floors can be installed in various ways, depending on the specific products and the installer's preference. They can be installed as floating floors, where the planks are attached to each other but not glued to the subfloor, or they can be glued down or nailed to the subfloor. It is important to follow the manufacturer's installation instructions or consult a professional installer.

ITEMNAME:

Lagos

- ITEMCODE: BDWF917728
- DIMENSIONS: 1900x180
- GRADE: DE
- GROOVE: D-click
- TREATMENT: Brushed, Waxed and oiled
- CLASS: Rustic
- PACKAGE: 2,736 m²
- THICKNESS: 15
- TOPLAYER: 4

Finishing: Oak Multi plank floors can be finished with various types of coatings to protect them and enhance their appearance. This can include a matte, satin, or high-gloss finish. Additionally, different color tones can be chosen, such as natural oak, dark brown, whitewashed, stained, or oiled.

Maintenance: Oak Multi plank floors require regular maintenance to keep them in good condition. This includes vacuuming or sweeping the floor to remove dust and dirt. It is also recommended to periodically clean the floor with a mild cleaning solution and a damp cloth. It is important to avoid excessive moisture as it can damage the wood.

Durability: Oak Multi plank floors are generally durable and long-lasting. The multi-layered construction provides added stability and makes the floor less susceptible to temperature and humidity changes. By choosing wood sourced from sustainably managed forests, you also contribute to environmental friendliness. It is always advisable to consult the specific product information from the manufacturer.

TECHNICAL SUPPORT

Our staff members are highly knowledgeable in their field. If you have any technical questions, please let us know!

SHORT LINES

From our sales office, we are in regular contact with our production team at the factory. This means quick responses and up-to-date information regarding orders.

TAILOR MADE SOLUTIONS

For projects that require a solution outside of our direct range, please contact our sales department.

Visit our website www.bamfloori.nl for more information about our products or services.

What is a multi-plank floor?



An oak wooden floor has been extremely popular for a long time. Within the flooring segment, it is the best-selling type of floor.

Multiplank is a technique that greatly reduces the movement of the wood. One of the most innovative products in the field of wooden flooring is 3-layer parquet. Laminate flooring is also referred to as multiplank flooring.

This floor combines all the advantages of a wooden floor while avoiding the drawbacks of solid wood flooring. Multiplank is a genuine wooden product, making it incomparable to laminate. The appearance and experience of multiplank are identical to that of parquet floors.

Acclimatization: Always allow a newly delivered BAMFLOORI floor to acclimate to the conditions of the room where it will be installed for a minimum of 24 hours. Differences in temperature and moisture can cause slight dimensional changes.

Properties

- Suitable for underfloor heating and/or cooling
- Floor shrinks or expands only minimal
- Less expensive than solid wood flooring
- Can be installed as a floating floor, even for larger areas
- Environmentally friendly as only the top layer consists of Oakwood
- Long lifespan
- Easy and fast installation without the need for glue.

BAMFLOORI
NATURAL FLOORING

Korte Stukken 8,
5371 MN Ravenstein,
The Netherlands
Telefoon +31 486 437 681